



SAFETY DATA SHEETS

M-21252/E-4

DATE: 21May2015

SUPPLIER ADDRESS: 1290 COMBERMERE STREET

TROY, MI 48083

EMERGENCY PHONE NUMBER: (248) 589-2950

1. CHEMICAL PRODUCT

PRODUCT NAME: CARBON DIOXIDE IN NITROGEN

SYNONYMS: None

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS#	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
CARBON DIOXIDE	CO2	124-38-9	.51-90 PCT	5000	5000	5000	30000
NITROGEN	N2	7727-37-9	BALANCE	S/A	S/A	S/A	S/A

Note: S/A = SIMPLE ASPHYXIANT

3. HAZARD IDENTIFICATION

*** EMERGENCY OVERVIEW ***
High pressure gas.

Can cause rapid suffocation.

Can increase respiration and heart rate.

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation

ACUTE EFFECTS: Exposure to carbon dioxide at 1-4% concentrations results in increased respiratory volume. Concentrations greater than 4% produce labored breathing and is dangerous for even a few minutes. Mixture can act as a simple asphyxiant by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, dizziness, nausea, vomiting, unconsciousness, and death.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY (US Only):

NTP - No

IARC MONOGRAPHS - No

OSHA REGULATED - No

4. FIRST AID MEASURES

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: None

SKIN CONTACT: None

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

5. FIRE FIGHTING MEASURES

FLASH POINT: Nonflammable

AUTOIGNITION TEMPERATURE: N/Av

FLAMMABLE LIMITS: Nonflammable

LOWER:

UPPER:

EXTINGUISHING MEDIA: Use what is appropriate for surrounding fire.

SPECIAL FIRE FIGHTING INSTRUCTION AND

EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing.

Keep fire exposed cylinders cool with water spray. If possible, stop the product flow.

HAZARDOUS COMBUSTION PRODUCTS: None

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Cylinder rupture may occur under fire conditions.

6. ACCIDENTAL RELEASE MEASURES

CLEAN UP PROCEDURES: Shut off source if possible and remove source of heat.

Remove leaking cylinder to exhaust hood or safe outdoor area if this can be done safely.

SPECIALIZED EQUIPMENT: None

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders.

PRECAUTIONS TO BE TAKEN IN STORAGE:
Store in well ventilated areas. Keep
valve protection cap on cylinders when
not in use.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentrations below exposure limits and to avoid asphyxiation.

PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses
SKIN PROTECTION: None
RESPIRATORY PROTECTION: In case of
leakage, use self-contained breathing
apparatus.
OTHER PROTECTIVE EQUIPMENT: Safety shoes
when handling cylinders.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless
ODOR: Odorless
PHYSICAL STATE: Gas
VAPOR PRESSURE: @20 deg.C: N/Ap
VAPOR DENSITY (AIR=1): 0.970-1.080
BOILING POINT (C): N/Ap
SOLUBILITY IN WATER: cm³/100cm³ H₂O:
1.485
SPECIFIC GRAVITY (H₂O=1): Gas
EVAPORATION RATE: Gas
ODOR THRESHOLD: None

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly
ventilated areas. Storage near a heat
source.

MATERIALS TO AVOID: Carbon dioxide
reacts with alkaline materials. Carbon
dioxide decomposes when heated above
1700 degrees celsius. Nitrogen reacts
with Li, Nd, and Ti at high
temperatures.

HAZARDOUS POLYMERIZATION: Will not
occur.

HAZARDOUS DECOMPOSITION: None

11. TOXICOLOGICAL INFORMATION

LETHAL CONCENTRATION (LC₅₀): None established
LETHAL DOSE 50 (LD₅₀): N/Ap
TERATOGENICITY: N/Ap
REPRODUCTIVE EFFECTS: N/Ap
MUTAGENICITY: N/Ap

12. ECOLOGICAL INFORMATION

No adverse ecological effects are expected.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

14. TRANSPORT INFORMATION

CONCENTRATION: 0.51-90%
DOT DESCRIPTION (US ONLY):
PROPER SHIPPING NAME: Compressed gas,
n.o.s.
HAZARD CLASS: 2.2 (nonflammable gas)
IDENTIFICATION NUMBER: UN1956
REPORTABLE QUANTITIES: None
LABELING: NONFLAMMABLE GAS
ADR/RID (EU Only): Class 2, 1A
SPECIAL PRECAUTIONS: Cylinders should be
transported in a secure upright position
in a well ventilated truck.

15. REGULATORY INFORMATION

OSHA: Process Safety Management: Minor component is not listed in appendix A of 29 CFR 1910.119 as a highly hazardous chemical.
TSCA: Mixture is not listed in TSCA inventory.
SARA: The threshold planning quantity

for material is 10,000 lbs.
EU NUMBER: N/Ap
NUMBER IN ANNEX 1 OF DIR 67/548: Mixture
is not listed in annex 1.
EU CLASSIFICATION: N/Av
R: 20
S: 9,23

16. OTHER INFORMATION

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS:

N/Ap - Not Applicable

N/Av - Not Available

SA - Simple Asphyxiant

NE - None Established

DISCLAIMER: Information included in this document is given to the best of our knowledge, however, no warranty is made that the information is accurate or complete. We do not accept any responsibility for damages by the use of the document.